

UNITED STATES PATENT APPLICATION

FOR

SYSTEM AND METHOD FOR MODULATION OF NON-DATA BEARING
CARRIERS IN A MULTI-CARRIER MODULATION SYSTEM

Inventors:

Ahmad Chini
Javad Omid
Hossein Alavi

Prepared by:

Blakely, Sokoloff, Taylor & Zafman LLP
12400 Wilshire Boulevard, Suite 700
Los Angeles, California 90025
(714) 557-3800

09883554-061601

SYSTEM AND METHOD FOR MODULATION OF NON-DATA BEARING CARRIERS IN A MULTI-CARRIER MODULATION SYSTEM

FIELD

5 [0001] The invention relates to the field of communications. In particular, one embodiment of the invention relates to a system and method for mitigating power spectral density irregularities through modulation of random data onto non-data bearing carriers.

10 GENERAL BACKGROUND

 [0002] For many years, a number of modulation techniques have been used to transfer data from a source to a destination. One type of modulation technique is referred to as multi-carrier modulation (MCM). In accordance with MCM, data is split into several data components and each of these data components is transmitted over
15 separate carriers so that each individual carrier has a narrower bandwidth than the composite signal. In general, a "carrier" is an electromagnetic pulse or wave transmitted at a steady base frequency of alternation on which information can be imposed. Of course, when used in connection with fiber optic medium, the carrier may be a light beam on which information can be imposed.

20 [0003] Currently, there exist a number of multi-carrier modulation schemes such as Orthogonal Frequency Division Multiplexing (OFDM) for example. OFDM subdivides the available spectrum into a number of narrow band channels (e.g., 100 channels or more). The carriers for each channel may be spaced much closer together than Frequency Division Multiplexing (FDM) based systems because each carrier is
25 configured to be orthogonal to its adjacent carriers. This orthogonal relationship may be achieved by setting each carrier to have an integer number of cycles over a symbol period. Thus, the spectrum of each carrier has a null at the center frequency of each of the other carriers in the system. This results in no interference between the carriers, allowing then to be spaced as close as theoretically possible.

30 [0004] In many instances, MCM systems are designed to avoid modulating information onto carriers that are unreliable, placing them in a "non-data bearing" state. The carriers are rendered unreliable when they are experiencing unfavorable channel characterizations such as fading, a high degree of interference and the like. Normally, a

carrier is determined to be "unreliable" based on channel measurements at the receiver. Since channel characterizations for each unreliable carrier may vary over time, they are periodically monitored through modulation of constant or alternating data (e.g., logic "0"s or "1"s) onto these carriers (i.e., an unreliable carrier is modulated with constant data). Non-data bearing carriers may also be used as pilot tones for channel estimation, timing and carrier recovery.

5 [0005] When using an Inverse Fast Fourier Transform (IFFT) to produce multiple carriers, constant or alternating data modulated carriers result in harmonics with concentrated energy at these non-data bearing carriers, which produce Power Spectral Density (PSD) irregularities or peaks at these carriers.

10 [0006] For example, as shown in Figure 1, a power spectrum of a transmit signal (e.g., a HOMEPLUG™ packet) using an OFMD modulation technique is illustrated. As shown, four carriers associated with channels 10, 20, 40 and 60 are modulated with constant data (e.g., "11" for Differential Quadrature Phase Shift Keying "DQPSK"). This causes PSD peaks 100, 110, 120 and 130 at those carriers rising approximately eight decibels (8 dB) above the power spectrum 140.

15 [0007] As a result, in order to comply with strict Federal Communication Commission (FCC) power level standards and avoid interference to other users of the band, the total power of the transmit signal must be reduced. This reduces signal quality (e.g., signal-to-noise ratio) detected at the receiver which, in turn, reduces coverage of the receiver, data throughput, and the like.

20 [0008] Thus, it would be advantageous to develop a modulation technique that mitigates PSD irregularities occurring at non-data bearing carriers.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The features and advantages of the present invention will become apparent from the following detailed description of the present invention in which:

[0010] Figure 1 is a power spectrum of a transmit signal (e.g., a
5 HOMEPLUG™ packet) using an OFMD modulation technique.

[0011] Figure 2 is an exemplary embodiment of a power spectrum of a composite transmit signal of Figure 1 produced by a multi-carrier modulation (MCM) system that modulates random data onto non-data bearing carriers.

[0012] Figure 3 is an exemplary embodiment of a communication network
10 utilizing the invention.

[0013] Figure 4 is an exemplary embodiment of internal logic of a MCM system.

[0014] Figure 5 is an exemplary embodiment of a general block diagram illustrative of logic within a first MCM system (transmitter) that modulates non-data
15 bearing carriers with random data for transmission to a second MCM system (receiver)

[0015] Figure 6 is an exemplary embodiment of operations between a transmitter and a receiver in accordance with non-data bearing carrier random modulation.

DETAILED DESCRIPTION

0983554-061601

[0016] Herein, various embodiments of the invention relate to a system and method for mitigating power spectral density irregularities through modulation of random data onto non-data bearing carriers, namely modulating each carrier currently in a non-data bearing state with random data. Herein, this “non-data bearing” state comprises a level of operation where a carrier is used for other purposes besides data transmission such as synchronization, carrier recovery, timing recovery, channel characterization, and may be also in an “unreliable” state when that carrier is experiencing unfavorable channel characterizations. Of course, non-data bearing carriers may also be used as pilot tones for channel estimation, timing and carrier recovery.

[0017] The embodiments described herein are not exclusive; rather, they merely provide a thorough understanding of the invention. Also, well-known circuits are not set forth in detail in order to avoid unnecessarily obscuring the invention.

[0018] In the following description, certain terminology is used to describe certain features of the invention. For example, “logic” includes hardware, firmware, software or any combination thereof that performs a desired function on input data. For example, in one embodiment, logic comprises a processing unit accessing software contained in memory to perform a non-data bearing carrier random data modulation scheme as described in greater detail in Figures 5-8. Examples of a “processing unit” include as a digital signal processor, a microprocessor, a micro-controller, an application specific integrated circuit (ASIC), a field programmable gate array, a state machine, combinatorial logic and the like.

[0019] In addition, a “link” is generally defined as one or more physical or virtual information-carrying mediums to establish a communication pathway. Examples of the medium include a physical medium (e.g., electrical wire, optical fiber, cable, bus traces, etc.) or a wireless medium (e.g., air in combination with wireless signaling technology). In one embodiment, the link may be an Alternating Current (AC) power line, perhaps routing information in accordance with a HOMEPLUG™ standard. One version of the HOMEPLUG™ standard is entitled “Release V0.8 Medium Interface Specification” published on or around May 25, 2001.

[0020] In general, a “non-data bearing” carrier may occur in any modulation scheme that produces a carrier or pilot tone that is used for other purposes besides data

transmission, such as synchronization, carrier recovery, timing recovery or channel characterization for example. Various applications may include, but are not limited or restricted to Orthogonal Frequency Division Multiplexing (OFDM), Frequency Division Multiple Access (FDMA), Spread Spectrum, Frequency Division Multiplexing (FDM) or even wavelet based modulation.

[0021] Referring to Figure 2, an exemplary embodiment of a power spectrum of a composite transmit signal produced by a multi-carrier modulation (MCM) system that modulates random data onto non-data bearing carriers is shown. The power spectrum 200 is produced for a composite transmit signal 210 having N carriers, where "N" is a positive integer ($N \geq 1$). As shown previously in Figure 1, the transmit signal 210 features non-data bearing carrier numbers 10, 20, 40 and 60, which are represented by labels 220, 230, 240 and 250, that are now modulated with random data. This method is referred to herein as "non-data bearing carrier random modulation." The "random data" may be either (1) truly random in nature and produced by a random bit generator or (2) pseudo-random in nature and produced by a pseudo-random bit generator.

[0022] As shown in Figure 2, the modulation of non-data bearing carriers with random data greatly mitigates the presence of power spectral density (PSD) irregularities at frequencies associated with non-data bearing carriers 220, 230 and 240 and 250. The reduction of PSD irregularities is due to the non-periodic nature of the modulated carrier. Thus, power is not concentrated at these portions of the power spectrum 200, but rather is continuously distributed.

[0023] Referring to Figure 3, an exemplary embodiment of a communication network utilizing the invention is shown. The communication network 300 comprises a plurality of MCM systems 310_1 - 310_M ($M \geq 1$) in communication with a network transceiver 320 via links 330_1 - 330_M . These links 330_1 - 330_M may be wired or wireless links. In addition, the network transceiver 320 may be further coupled to a link 340 operating as networking lines for an establishment (e.g., residence, apartment building, place of business, etc.) as shown. For instance, the link 340 may be electrical wiring (e.g., AC power line) which data is transmitted over such wiring in accordance with current or future HOMEPLUG™ standards. Examples of the "network transceiver" include a computer (e.g., gateway, server, etc.), a router, a switching device, a wireless networking access point (e.g., WLAN access point). Of course,

although not shown, one or more of the MCM systems 310₁-310_M may be configured to communicate with other MCM system(s) acting as transceiver(s).

5 [0024] Each MCM system 310₁,..., or 310_M is a product that supports the non-data bearing carrier random modulation scheme, namely the modulation of reliable carriers with the data to be transmitted and the modulation of the non-data bearing carriers with random data. The modulated carriers are transmitted over a composite channel to the network transceiver 320 (or another MCM system) acting as a receiver. Examples of certain types of MCM systems include various types of MCM modems (wired or wireless), a computer with wireless connectivity (e.g., a gateway or server,
10 hand-held "PDA", a data terminal, laptop, desktop, etc.), a set-top box, a network appliance, a wireless communication device (e.g., phones, pager, etc.) and the like.

[0025] Referring now to Figure 4, an exemplary embodiment of internal logic of a MCM system is shown. The MCM system 310_x includes a processing unit 400, an internal memory 410 and a transceiver 420. Configured as any readable storage
15 device such as a magnetic, optical, or semiconductor storage medium, the internal memory 410 may be either physically independent from the processing unit 400 or integrated within the processing unit 400. In one embodiment, the internal memory 410 may be implemented as any type of non-volatile memory such as flash memory, hard disk, on-chip ROM and the like. Of course, it is contemplated that the internal
20 memory 410 may include volatile memory or a combination of volatile and non-volatile memory. The internal memory 410 stores multi-carrier modulation software, which enables the processing unit 400 to perform non-data bearing carrier random modulation. Of course, it is contemplated that the MCM system 310_x does not require memory if its non-data bearing carrier random modulation functionality is hard-wired.

25 [0026] The transceiver 420 enables modulated carrier signals to be output over a link and destined for receipt by the network transceiver 320 of Figure 3 or perhaps another MCM system (not shown). The transceiver 420 further enables channel characterization data to be received from the network transceiver 320 (or another MCM system) as well.

30 [0027] Referring to Figure 5, an exemplary embodiment of a general block diagram illustrative of logic within a first MCM system (transmitter) 500 (e.g., MCM system 310_x) that modulates non-data bearing carriers with random data for transmission to a receiver system 550 (e.g., a second MCM system, network transceiver 320 of Figure 3, etc.) is shown. For this embodiment, the first MCM system 500

comprises a multiplexer unit 510, a multi-carrier modulator 520 and a feedback link 530. A (pseudo) random bit generator 540 may be implemented within the first MCM system 500 as represented by dashed lines. The receiver system 550 includes a multi-carrier demodulator 560 and a channel estimator 570. These systems 500 and 550

5 communicate over a channel link 580.

[0028] Herein, the feedback link 530 provides data from the channel estimator 570 of the receiver system 550 as to which carriers of a transmit signal, if any, possess channel characterization that would cause them to be deemed to exist in an unreliable state. For example, the channel estimator 570 may operate in accordance

10 with blind channel estimation (no knowledge of the transmitted data is required) or data based channel estimation (knowledge of the transmitted data is required so pseudo-RNG used). Both types of channel estimation may analyze signal-to-noise ratio (SNR), bit error rate (BER) and/or other signal characteristics of each carrier. The channel characterization of each carrier may be carried out by observing the general

15 characteristics of the signal such as SNR (blind) or by observing the quality of the values transferred to the receiver system (data based) 550 and/or comparing them to values previously stored therein. For example, the transmit signal may be transferred in an encoded format, decoded at the receiver system 550 and re-encoded for comparison with the original received signal.

[0029] The multiplexer unit 510 uses the data provided from the channel estimator 570, which is referred to as "carrier map," to select which output ports

20 $511_1, \dots, 511_R$ provide desired transmission data or random data. Perhaps, as an option, the number of output ports corresponding to the number of carriers forming the transmit signal as shown (e.g., $R=N$). For clarity, as represented by dashed lines,

25 outputs from ports $511_i, 511_j$ and 511_k (where $i \neq j \neq k$) are random data because these carriers are non-data bearing and even deemed to be unreliable. Thus, the input ports $521_i, 521_j$ and 521_k of the multi-carrier modulator 520 receive random data in lieu of transmission data. This causes the $i^{\text{th}}, j^{\text{th}}$ and k^{th} carriers to be modulated with the random data and transmitted from output port 522 over channel link 580 as part of the

30 transmit signal to the receiver system 550. The $i^{\text{th}}, j^{\text{th}}$ and k^{th} carriers are modulated in accordance with OFDM, FDMA, Spread Spectrum, FDM, wavelet based or other types of modulation techniques.

0988354-061601

[0030] Referring now Figure 6, an exemplary embodiment of the operations between a transmitter and a receiver in accordance with non-data bearing carrier random modulation is shown. Initially, the transmitter (e.g., first MCM system) sends a channel information request to the receiver (e.g., second MCM system, network transceiver, etc.) to characterize all carriers associated with the channel link (block 600). In response to receiving the channel information request, the receiver analyzes the received signal and characterizes the data placed on each carrier (block 610). Such characterization may be through analysis of the SNR, BER, and the like. Thereafter, the receiver determines which carriers are in an unreliable state and outputs a carrier map over the feedback link to the transmitter (blocks 620 and 630). The carrier map indicates to the transmitter which carriers are deemed to be unreliable so that no data is placed on to such carriers. In addition, the carrier map is used by the transmitter to control placement of random data on to those non-data bearing carriers.

[0031] While certain exemplary embodiments have been described and shown in the accompanying drawings, it is to be understood that such embodiments are merely illustrative of and not restrictive on the broad invention, and that this invention not be limited to the specific constructions and arrangements shown and described, since various other modifications may occur to those ordinarily skilled in the art. For example, it may be possible to implement the invention or some of its features in hardware, firmware, software or a combination thereof.